



Castrol Engine Shampoo

Helping maintain engine power and efficiency

Description

Modern driving creates combustion by-products that can build up in your oil. When these accumulate, they build up to form layers of sludge that can harm engine performance, especially in the latest precision engines.

Castrol "Engine Shampoo" helps to maintain engine power and efficiency. By adding it to the old engine oil and running the engine for ten minutes on idle before changing the oil, sludge and dirt is then removed with the old oil when changed

Application

Castrol "Engine Shampoo" is suitable for use in automotive gasoline and light duty diesel engines as part of routine oil changes.

Conditions of Use

Usage / Precautions

1. Warm-up the engine before use to get the oil to operating temperature
2. Stop the engine and add 300ml of "Engine Shampoo" to the existing engine oil through the filler cap.
3. Re-start and idle the engine for approximately ten minutes.
4. Stop the engine and drain the used engine oil and engine shampoo.
5. Change the oil filter and fill with new engine oil.

- Do not add to gasoline or diesel fuel systems.
- Do not drive with the used engine oil containing "Engine Shampoo".
- Caution should be taken with hot engine oil when changing
- Add 300ml of "Engine Shampoo" for each 3 – 6 litre oil capacity. (check the engine oil capacity in your owner's manual)
- This product may freeze under extreme cold conditions.
- Do not use in Rotary or 2-stroke engines
- For use on inside of engine only. Do not use for cleaning external surfaces or skin

Advantages

- Parts-friendly solvent free formulation, designed specifically not to harm engine seals and other parts
- This innovation – Castrol Powerful Cleaning Agent (PCA) - is so powerful it can even dissolve away sludge that has already formed in your engine.
- Helps maintain engine power and efficiency by removing dirt and sludge from engine parts and keeping oil galleries clear
- It's very simple to use: Add Castrol "Engine Shampoo" to the engine just before changing the oil, run the engine for ten minutes on idle, drain and refill with fresh oil

Typical Characteristics

Name	Method	Units	Castrol Engine Shampoo
Density @ 15C, Relative	ASTM D4052	g/ml	0.88
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	11.3
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	77
Viscosity Index	ASTM D2270	None	138
Pour Point	ASTM D97	°C	-33
Flash Point, PMCC	ASTM D93	°C	208

Product Performance Claims

Powerful Cleaning Agent "PCA" provides superior cleaning performance.

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol Engine Shampoo

06 Feb 2020

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

Orders/Enquiries: 0345 6008125 Technical Enquiries: 0345 082 1719 BP (Ireland) Ireland Orders/Enquiries: 1850 930 3942 Ireland Technical Enquiries: 1800 509 353

www.castrol.com/uk